

(12) INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(19) World Intellectual Property Organization
International Bureau(43) International Publication Date
3 July 2003 (03.07.2003)


PCT

(10) International Publication Number
WO 03/055246 A1

- (51) International Patent Classification⁷: **H04Q 7/32**, **H04B 7/26**
- (74) Agents: **PIOTROWICZ, Pawel** et al.; Verner, Shipley & Co., 20 Little Britain, London EC1A 7DH (GB).
- (21) International Application Number: **PCT/EP01/15395**
- (22) International Filing Date:
21 December 2001 (21.12.2001)
- (25) Filing Language: **English**
- (26) Publication Language: **English**
- (71) Applicant (for all designated States except US): **HI-TACHI, LTD** [JP/JP]; 6 Kanda-Surugadai 4-chome, Chiyoda-ku, Tokyo, Tokyo 101-8010 (JP).
- (72) Inventors; and
- (75) Inventors/Applicants (for US only): **TAKATANI, Yukihiko** [JP/FR]; 23 Avenue Justinia, F-06400 Cannes (FR). **NONAKA, Naomichi** [JP/FR]; 27, route des Breguieres, F-06110 Le Cannet (FR). **HAYASHI, Masato** [JP/FR]; 140, Rue d'Antibes, F-06400 Cannes (FR).
- (81) Designated States (national): AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NO, NZ, OM, PH, PL, PT, RO, RU, SD, SE, SG, SI, SK, SL, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VN, YU, ZA, ZM, ZW.
- (84) Designated States (regional): ARIPO patent (GH, GM, KH, LS, MW, MZ, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, CH, CY, DE, DK, ES, FI, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE, TR), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

[Continued on next page]

(54) Title: MOBILE COMMUNICATIONS NETWORK USING MOBILE STATION WITH RELAY-FUNCTION AND METHOD FOR REWARDING RELAY ACTIVITIES OF MOBILE STATION



(57) Abstract: A GSM network (1) includes a base station (2). A first mobile terminal (5) is outside a region of coverage. A second terminal (6) relays signals between the first terminal and the base station or a third terminal (7). The second terminal is awarded credit for relaying the signals.

WO 03/055246 A1

WO 03/055246 A1



Published:

— with international search report

For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.

MOBILE COMMUNICATION NETWORK USING MOBILE STATION WITH RELAY-FUNCTION AND METHOD FOR REWARDING RELAY ACTIVITIES OF MOBILE STATION

Field of the Invention

The present invention relates to a mobile communications network.

Background art

5 A fixed communication network generally allows data or voice to be communicated between fixed terminals. An example of such a network is a public switched telephone network (PSTN) in which subscribers communicate using fixed telephone
10 sets. Other examples include wired local-area networks (LANs) and wide-area networks (WANs), which are mainly used for transmission of data between computers. Fixed communication networks tend to restrict mobility of the users. If the user moves, they often have little choice but to disconnect their terminal from the network and reconnect at a different location. This is inconvenient for the user
15 since network connection is temporality lost. Moreover, network reconnection is not without its problems, particularly as it requires a connection point at the new location.

A mobile communication network helps to overcome these problems. An example
20 of such a network is a public land mobile network (PLMN) such as the global system for mobile communication (GSM) network. Mobile terminals exchange signals with geographically-spaced base stations included in the network using radio signals. This allows the user to make and receive calls within a large area, even while moving. Mobility is achieved not only because wireless connections are used,
25 but also because the mobile terminal is dynamically allocated a suitable base station. Thus, if the user is moving, a connection to one base station can be dropped and a new connection to another base station can established automatically so as to provide seamless coverage.

30 Mobile communication networks and mobile terminals are becoming increasingly common. For example, so-called 2nd generation mobile telecommunication systems, such as GSM networks, are being replaced by 3rd generation systems, such as universal mobile telecommunications standard (UMTS) networks. Moreover, users

are becoming more reliant on their mobile terminals. Therefore, it is important that users are able to access the mobile communications network freely.

However, access can be restricted by the connections provided by base stations.

5 For example, at a physical level, a radio link between the terminal and the base station may be of poor quality. This can happen when the user is located indoors. Alternatively, at a resource level, the base station may not be able to provide sufficient channels to mobile terminals requiring service. This often occurs when a large number of people gather at one place, for example at a sports stadium.

10

A solution to this problem is to provide additional base stations. However, this solution is expensive and relies upon being able to find suitable sites for the additional base stations.

15 Another solution is to employ mobile terminals as relays. For example, "On the Relaying Capability of Next-Generation GSM Cellular Networks" by George Neonakis Aggélou and Rahim Tafazolli, pp. 40-47, IEEE Personal Communications (February 2001) describes a terminal which is able to relay data using an ad-hoc GSM (A-GSM) network.

20

The present invention seeks to provide an improved mobile communications network for mobile terminals.

Summary of the Invention

25 According to the present invention there is provided a mobile communications network for mobile terminals including a fixed station for exchanging signals with a first mobile terminal, a second mobile terminal configured to relay signals between said fixed station and said first mobile terminal wherein the network is configured to store information relating to use of the second mobile terminal as a relay.

30

This has the advantage that use of the second mobile as a relay may be monitored and rewarded.

The network may be configured to store or continue to store said information subsequent to completion of said relay. The network may include a server wherein said information is stored at said server. The information may be stored at the second mobile terminal.

5

The information may include a value of credit for relaying said signals. The credit may be redeemable. The network may be configured to provide said second mobile terminal with a service in response to redemption of said credit.

10 The network may include a subsidiary mobile communications network for relaying said signals between the fixed station and said first mobile network. The second mobile terminal may include a router for forwarding signals between said fixed station and said first mobile terminal. The router may be configured to operate according to Internet Protocol.

15

The network may include a third mobile terminal configured to relay signals between said fixed station and said first mobile terminal.

20 The network may be configured to store information relating to previous use of said second mobile as a relay. The network may be configured to accumulate information relating to use of said second mobile as a relay.

25 According to the present invention there is also provided a method of mobile communication in a mobile communications network including a fixed station for exchanging signals with a first mobile terminal, the method comprising using a second mobile terminal to relay signals between said fixed station and said first mobile terminal and storing information relating to use of the second mobile as a relay.

30 According to the present invention there is still further provided a mobile terminal for communication with a fixed station included in a mobile communications network, said mobile terminal being configured to relay signals between said fixed

station and another mobile terminal and to provide information to said network relating to its use as a relay.

The terminal may include a first wireless interface for communicating with said
5 fixed station. The terminal may include a second, different wireless interface for communicating with said other mobile terminal.

According to the present invention there is yet further provided a server associated with a mobile communications network for storing information relating to mobile
10 terminals, said server configured to store relay information in response to a first mobile terminal exchanging signals with a fixed station included in said network via a second mobile terminal.

According to the present invention there is still further provided a method, in a
15 mobile communications network, of rewarding a first mobile terminal for relaying signals between a second mobile terminal and either a third mobile terminal or a fixed station, the method comprising awarding credit to said first mobile terminal, wherein said credit is exchangeable for money or money's worth.

20 The money's worth may include provision of communication service.

According to the present invention there is also provided a mobile communications network for mobile terminals including a first mobile terminal for relaying signals between a second mobile terminal and either a third mobile terminal or a fixed
25 station, the network being configured to award credit to said first mobile terminal, wherein said credit is exchangeable for money or money's worth, so as to reward said first mobile terminal for relaying said signals.

The network may be configured to store information relating to said credit awarded.
30

According to the present invention there is further provided a server associated with a mobile communications network which includes a first mobile terminal for relaying signals between a second mobile terminal and either a third mobile terminal

or a fixed station, the server being configured to award credit to said first mobile terminal, wherein said credit is exchangeable for money or money's worth, so as to reward said first mobile terminal for relaying said signals.

5 According to the present invention there is also provided a mobile terminal for use in mobile communications network and for relaying signals between another mobile terminal and either yet another mobile terminal or a fixed station, said terminal being configured to award itself or be awarded credit for relaying said signals, wherein said credit is exchangeable for money or money's worth.

10

According to the present invention there is provided a method, in a mobile communications network, of rewarding a first mobile terminal for relaying signals between a second mobile terminal and either a third mobile terminal or a fixed station, the method comprising extending call-time of said first mobile terminal.

15

According to the present invention there is provided a method of operating a mobile communications network including a first mobile terminal for relaying signals between a second mobile terminal and either a third mobile terminal or a fixed station, the method comprising rewarding the first mobile terminal for

20

relaying said signals with increased network access.

The rewarding of the first mobile terminal with increased network access may comprise increasing call-time or data volume available to the first mobile terminal.

25 Brief description of the Drawings

Embodiments of the present invention will now be described, by way of example, with reference to the accompanying drawings in which:-

Figure 1 shows a mobile communications network and mobile terminals according to a first embodiment of the present invention;

30 Figure 2 is a schematic block diagram of a mobile terminal shown in Figure 1;

Figure 3 is a schematic block diagram of a server shown in Figure 1;

Figure 4 illustrates a first type of table held by the server of Figure 1;

Figure 5 illustrates a second type of table held by the server of Figure 1;

Figure 6 is a process flow diagram showing a first procedure by which a first terminal, using a second terminal as a relay, is connected to a third terminal;

Figure 7 is a process flow diagram showing a second connection procedure;

Figure 8 is a process flow diagram showing a first procedure by which

5 communication is terminated;

Figure 9 is a process flow diagram showing a second termination procedure;

Figure 10 is a process flow diagram showing a third termination procedure;

Figure 11 shows a display of a mobile terminal whose signals are being relayed by another terminal;

10 Figure 12 shows a mobile communications network and mobile terminals according to a second embodiment of the present invention and

Figure 13 is a process flow diagram showing a procedure by which a first terminal, using two terminals as relays, is connected to another terminal.

15 Preferred Embodiments of the Invention

Referring to Figure 1, in a first embodiment of the present invention, a mobile communications network 1 includes first and second base stations 2, 3. In this example, the network 1 is a public land mobile network (PLMN), such as a GSM network. The network 1 includes a server 4 for logging network use and will be
20 described in more detail later.

A description of a GSM network can be found in "The GSM System for Mobile Communications" by Michel Mouly and Marie-Bernadette Pautet (Cell & Sys, Palaiseau, 1992).

25

First, second, third and fourth mobile terminals 5, 6, 7, 8 are suitable for use with the network 1. Each terminal 5, 6, 7, 8 can be used to communicate with other mobile terminals or, via an additional fixed communications network (not shown), with fixed terminals (not shown). For example, the fixed communications network
30 can be a public switched telephone network.

A problem can sometimes arise that the first mobile terminal 5 is temporarily unable to use the communications network 1. There may be two reasons for this:

Firstly, the terminal 5 may be unable to use the network 1 because wireless signals received at the terminal 5 from a base station or those received at a base station from the terminal 5 are too weak. This usually occurs if the terminal 5 is located
5 outside an area of coverage provided by the communications network's base stations or if the terminal 5 is located inside a building. Interference from another source can also render wireless signals unusable, i.e. the signals are too noisy.

Secondly, the terminal 5 may not be able to use the network 1 in that, despite there
10 being strong enough signals, there is no communication channel available. For example, the terminal 5 may be located within an area of coverage provided by a third base station (not shown) which has already allocated all its communications channels to other mobile terminals. This often occurs if there is a high density of mobile terminals.

15 A solution to this problem is to employ the second mobile terminal 6 as a relay. The second terminal 6 effectively expands coverage provided by the network 1. The first mobile terminal 5 benefits from this arrangement since it is provided with service that it would otherwise not have. The second mobile terminal 6 can also
20 benefit from this arrangement by being "paid" for use of its resources. As will be explained in more detail later, more than one mobile terminal can be used as a relay.

Referring to Figure 2, each mobile terminal 5, 6, 7, 8 includes a CPU 9, memory 10, display 11, first wireless interface 12 which comprises a modulator 13 and an
25 antenna 14, second wireless interface 15, which comprises a modulator 16 and an antenna 17 and a routing module 18 for routing data to one of the wireless interfaces 12, 15. The terminals 5, 6, 7, 8 may also include an input/output 19 for exchanging data over wired networks (not shown), a data input 20, such as keypad or touch sensitive screen, a microphone 21 and a speaker 22. Data is exchanged
30 between these elements 10, 11, 13, 16, 19, 20, 21, 22 using a bus 23.

The first wireless interface 12 is configured to exchange signals with the mobile communications network 1, which in this case is a GSM network. The second

wireless interface 14 is configured to exchange signals through a subsidiary mobile communications network (not shown). In this example, the subsidiary network is an ad-hoc wireless network according to the Bluetooth™ specification. Thus, the subsidiary wireless interface may comprise a Bluetooth transceiver chip. In this
5 example, coverage provided by the network 1 is greater than the subsidiary network. For example, a GSM base station may provide coverage in a cell with a radius of a few kilometres provided there are no obstacles. Bluetooth transceiver chips typically have a range less than a hundred meters. However, users often are located indoors where GSM network coverage is poor, but connection to at least one
10 Bluetooth chip is possible. Routing is conducted according to Internet Protocol (IP).

It will be appreciated that other wireless networks and corresponding interfaces can be used. However, the network 1 and the subsidiary network can be one and the
15 same and so a single wireless interface could be used.

Details relating to GSM can be found in "The GSM System for Mobile Communications" *supra*.

20 A system specification (Version 1.0) and a system overview may be found on the world-wide web at www.bluetooth.org or obtained from Bluetooth SIG, c/o Daniel Edlund, facsimile number +46 70 615 9049.

Referring to Figure 3, the server 4 monitors and records use of terminals 5, 6, 7, 8
25 as and when they are used to relay signals. The server 4 includes a CPU 24, memory 25, storage 26, such as a hard-disk drive, and a network controller 28, which exchange data through a bus 29.

Referring to Figure 4, storage 26 holds a user database 30 including information
30 relating to each user registered to use the network 1. The user information includes user ID 30, communications charges incurred 32 and credit 33 accumulated arising from use of the mobile terminal as a relay. Credit may be awarded according to different criteria, such as the length of time of a terminal is used as a relay, a

number of packets passing through the terminal, a number of times the terminal is used as a relay and/or power consumed. Credit 33 may be offset against charges, used for increased network access, used to obtain gifts or acquire some other benefit. Network access may be increased according to time and/or volume. It includes providing free calls, increased call-time and increased data volume. Charge offset includes providing rate discounts. Thus, there is an incentive for a user to allow their mobile terminal to be used as a relay.

Credit information 33 may also be held in memory 10 (Figure 2) of each respective mobile terminal 5, 6, 7, 8. Credit information 33 can be updated periodically, following a relay or on-demand. This allows the user to find out how many points 33 have been accumulated.

Referring to Figure 5, storage 26 also holds a relay information table 34 including information relating to communication sessions in which one or more mobile terminals are used as a relay. The session information includes a session number 35, the identities of the terminals 36, 37, start and end times 38, 39 and identities of mobile terminals used as relays 40, 41. It will be appreciated that other information may be stored.

A process by which the second mobile terminal 6 is used to relay signals between the first mobile terminal 5 and the first base station 2 will now be described.

Referring to Figure 6, the first mobile terminal 5 attempts to establish contact with the third mobile terminal 7 through the mobile communications network 1. Thus, in this case the first mobile terminal 5 is deemed to be a source terminal and the third mobile terminal 7 is taken to be a destination terminal. The first terminal 5 establishes whether a base station 2, 3 is contactable and, if so, whether a communication channel is available (step S1). If either limb of this test fails, then the first mobile terminal 5 establishes whether another mobile terminal 6, 7, 8 is prepared and able to act as a relay. Using the subsidiary communications network (not shown), the first mobile terminal 5 establishes a connection with the second mobile terminal 6 and sends a relay request (step S2). The second mobile terminal 6

establishes whether a base station 2, 3 is contactable and, if so, whether a communication channel is available (step S3). In this case, the second mobile terminal 6 is provided with service by the first base station 2. Therefore, the second terminal 6 replies to the first mobile terminal 5 indicating that it is prepared to relay signals between the first terminal 5 and the first base station 2 (step S4).

The first terminal 5 sends information relating to the identity of the source and destination terminals, namely the first and third terminals 5, 7 respectively, to the second terminal 6 over the subsidiary network (step S5). The second terminal 6 sends a message to the server 4, through the first base station 2 (Figure 1) via the network 1 (Figure 1) (step S6). The message includes information relating to the identity of the source and destination terminals and the identity of the relay terminal. The server 4 sends a message to the third terminal 7 indicating that the first terminal 5 wishes to establish a connection (step S7). In this example, it is assumed that the third terminal 7 is provided with service by the second base station 3.

If the third terminal 7 agrees to the connection with the first terminal 5, it sends an acknowledgement to the server 4 (step S8). The server 4 thereafter starts a timer (step S9). The acknowledgement is transmitted through the network 1 to the second terminal 6 (step S10), which in turn transmits the acknowledgement through the subsidiary network to the first terminal (step S11). A channel between the first and third terminals 5, 7 is opened allowing the terminals 5, 7 to communicate (step S12).

Thus, the first and third terminals 5, 7 communicate using the second terminal 6 as a relay. The routing module 18 of the second terminal 6 is responsible for directing data received by the first wireless interface 12 and feeding it to the second wireless interface 15 and *vice versa*.

The user of the second terminal 6 may still be able to make and receive calls or send and receive data even while being used as a relay by the first terminal 5. This can be achieved using time division multiple access (TDMA), wherein TDMA slots are

allocated for the terminal's own use and different TDMA slots are allocated for use by another terminal. It will be appreciated that the second terminal 6 may be able to relay signals for a plurality of terminals simultaneously.

- 5 Another process by which the second mobile terminal 6 is used to relay signals between the first mobile terminal 5 and the first base station 2 will now be described. In this case, a connection is initiated by the third terminal 7.

Referring to Figure 7, the first mobile terminal 5 checks whether it is can be
10 serviced by the mobile communications network 1. The first terminal 5 establishes whether a base station 2, 3 is contactable. It may also check whether a communication channel is available (step S13). If no base station 2, 3 is contactable, the first mobile terminal 5 establishes whether another mobile terminal 6, 7, 8 is prepared and able to act as a potential relay. Using the subsidiary mobile
15 communications network (not shown), the first mobile terminal 5 establishes a connection with the second mobile terminal 6 and sends a relay request (step S14). The second mobile terminal 6 establishes whether a base station 2, 3 is contactable and, if so, whether a communication channel is available (step S15). In this case, the second mobile terminal 6 is provided with service by the first base station 2.
20 Therefore, the second terminal 6 replies to the first mobile terminal 5 indicating that it is prepared to relay signals between the first terminal 5 and the first base station 2 (step S16). The second terminal 6 notifies the server 4 that signals intended for the first terminal 5 can be directed through the second terminal 6 (step S17). This is stored in the relay information table 34 (Figure 5).

25

The first terminal 5 can perform this check periodically, for example every few seconds. Alternatively, the terminal 5 can send a relay request through the subsidiary network as soon as it detects that it is no longer provided with service by the network 1.

30

The third mobile terminal 7 attempts to establish contact with the first mobile terminal 5 through the network 1. Thus, in this case the third mobile terminal 7 is deemed to be the source terminal and the first mobile terminal 5 is deemed to be

the destination terminal. The third terminal 7 transmits a message including information relating to the identity of the source and destination terminals to the server 4 using the network 1 (step S18). The server 4 looks-up who is relaying signals to the first terminal 5 in the relay information table 34. The server 4
5 thereafter sends a message, indicating that the third terminal 5 wishes to establish a connection with the first terminal 5, to the second terminal 5, through the network 1 (step S19). The second terminal 6 relays the message to the first terminal 5 using the subsidiary network (step S20).

10 If the first terminal 5 agrees to the connection with the third terminal 7, it sends an acknowledgement to the server 4 via the second terminal (steps S21 & S22). The server 4 starts a timer (step S23) and transmits the acknowledgement to the third terminal 7 (step S24). A channel between the first and third terminals 5, 7 is opened allowing the terminals 5, 7 to communicate (step S25).

15

The processes described earlier are concerned with establishing a communication between the first and third terminals 5, 7. Processes by which communication is ended by any of the terminals 5, 6, 7 involved will now be described.

20 Referring to Figure 8, if the first terminal 5 ends communications, it sends an end notification message to the second terminal 6 over the subsidiary network (step S26). The second terminal 6 passes on this message to the server 4 (step S27). The second terminal 6 can also send other information relating to its use as a relay, such as time spent relaying, number of packets relayed, amount of power consumed etc.
25 The server 4 stops its timer and notifies the third terminal that communication has ended (step S29).

Referring to Figure 9, if the third terminal 7 ends communication, it sends an end notification message to the server 4 (step S30). The server 4 stops its timer and
30 passes on this message to the second terminal 6 (step S31). The second terminal 6 then notifies the first terminal 31 that communication has ended (step S32). Optionally, the second terminal 6 can return a message to the server 4 with information relating to its use as a relay.

Referring to Figure 10, if the second terminal 6 ends communication, it sends an end notification message to the first terminal 5 (step S34) and also to the server 4 (step S35). As above, the second terminal 6 can include information in the message
5 relating to its use as a relay.

When the server 4 stops its timer or receives information relating to a relay terminal it updates the user database 30 (Figure 4), for example adding communication charges to the first terminal's account and adding relay points to the second
10 terminal's account.

Referring to Figure 11, whenever a terminal 5, 6, 7, 8 uses another terminal as a relay, the display 10 indicates this fact. The relay terminal may also indicate that it is being used as a relay.
15

Referring again to Figure 2, each mobile terminal 5, 6, 7, 8 may optionally be provided with a relay management module (not shown). This allows either the user or the terminal itself to choose whether the terminal can be used as a relay. For example, the user can select an option in a menu indicating that they are prepared to
20 allow their terminal to be used. In another example, relay may be permitted provided there is sufficient battery charge.

In the embodiment described earlier, only one terminal is used as a relay. However, more than one terminal can be used.
25

A process by which the second and fourth mobile terminals 6, 8 are used to relay signals between the first mobile terminal 5 and the first base station 2 will now be described.

30 Referring to Figures 12 and 13, the first mobile terminal 5 attempts to establish contact with the third mobile terminal 7 through the mobile communications network 1. The first terminal 5 establishes whether a base station 2, 3 is contactable and, if so, whether a communication channel is available (step S38). If either limb

of this test fails, then the first mobile terminal 5 establishes whether another mobile terminal 6, 7, 8 is prepared and able to act as a relay. Using the second mobile communications network (not shown), the first mobile terminal 5 establishes a connection with the fourth mobile terminal 8 and sends a relay request (step S39).

- 5 The fourth mobile terminal 8 establishes whether a base station 2, 3 is contactable and, if so, whether a communication channel is available (step S40). In this case, the fourth mobile terminal 8 is not provided with service. Therefore, still using the second mobile communications network (not shown), the fourth mobile terminal 8 establishes a connection with the second mobile terminal 7 and sends a relay request
10 (step S41). The second mobile terminal 6 establishes whether a base station 2, 3 is contactable and, if so, whether a communication channel is available (step S42). In this case, the second mobile terminal 6 is provided with service by the first base station 2. The second terminal 6 replies to the fourth mobile terminal 8 indicating that it is prepared to relay signals between it and the first base station 2 (step S43).
15 In turn, the fourth terminal 8 replies to the first terminal 5 indicating that it is able to relay signals between it and the first base station (step S44).

The first terminal 5 sends information relating to the identity of the source and destination terminals, namely the first and third terminals 5, 7 respectively, to the
20 fourth terminal 6 (step S45). The fourth terminal 6 sends a message to the second terminal 6 (step S46). The message includes information relating to the identity of the source and destination terminals and the identity of a first relay terminal, namely the fourth terminal 8. The second terminal 8 sends a message to the server 4 (step S47). The message includes information relating to the identity of the source and
25 destination terminals, the identity of the first relay terminal and identifies itself as a second relay terminal.

The server 4 sends a message to the third terminal 7 indicating that the first terminal 5 wishes to establish a connection (step S48). If the third terminal 7 agrees
30 to the connection with the first terminal 5, it sends an acknowledgement to the server 4 (step S49). The server 4 thereafter starts a timer (step S50). The acknowledgement is transmitted through the network 1 to the second terminal 6 (step S51), which in turn transmits the acknowledgement through the second

network (not shown) to the first terminal 5, via the fourth terminal 6 (steps S52 & 53). A channel between the first and third terminals 5, 7 is opened allowing the terminals 5, 7 to communicate (step S54).

- 5 Thus, the first and third terminals 5, 7 communicate using the second and fourth terminals 6, 8 as a relay. The server 4 not only records use of the second terminal 6 as a relay, but also use of the fourth terminal 8.

10 It will be appreciated that the terminals may be configured to operate according to protocols designed to handle conflicts between two terminals which receive a relay request and which compete to be the relay, for example on a "first come-first served" basis. The terminal may be configured to search for the shortest route between a terminal and a base station.

- 15 If two or more relay routes are available to a terminal, then the terminal can store these routes, including information regarding the identity of relays, in a routing table. The terminal chooses a route and communicates with a base station. However, should transmission through the chosen route fail, for example due to relocation of the relay or introduction of an obstacle, the terminal can select
20 another route.

It will be appreciated that both the source and destination terminals may benefit from using relays. Thus, coverage may be extended to the source terminal by one or more relay terminals, while coverage may also be extended to an intended
25 destination terminal by one or more other relay terminals.

It will be appreciated that many modifications may be made to the embodiment hereinbefore described. For example, any type of mobile communications networks may be used.

Claims

1. A mobile communications network (1) for mobile terminals including:
a fixed station (2) for exchanging signals with a first mobile terminal (5);
5 a second mobile terminal (6) configured to relay signals between said fixed station and said first mobile terminal; and **characterised in that**
the network is configured to store information (30) relating to use of the second mobile terminal as a relay.
- 10 2. A network according to claim 1, which is configured to store or continue to store said information subsequent to completion of said relay.
3. A network according to claim 1 or 2, further including a server wherein said information is stored at said server.
- 15 4. A network according to any preceding claim, wherein said information is stored at the second mobile terminal.
5. A network according to any preceding claim, wherein said information
20 includes a value of credit for relaying said signals.
6. A network according to claim 5, wherein said credit is redeemable.
7. A network according to claim 6, which configured to provide said second
25 mobile terminal with a service in response to redemption of said credit.
8. A network according to any preceding claim, including a subsidiary mobile communications network for relaying said signals between the fixed station and said first mobile network.
- 30 9. A network according to any preceding claim, wherein said second mobile terminal includes a router for forwarding signals between said fixed station and said first mobile terminal.

10. A network according to claim 9, wherein said router is configured to operate according to Internet Protocol.
- 5 11. A network according to any preceding claim, including a third mobile terminal configured to relay signals between said fixed station and said first mobile terminal.
12. A network according to any preceding claim, which is configured to store
10 information relating to previous use of said second mobile as a relay.
13. A network according to any preceding claim, which is configured to accumulate information relating to use of said second mobile as a relay.
- 15 14. A method of mobile communication in a mobile communications network including a fixed station for exchanging signals with a first mobile terminal, the method comprising using a second mobile terminal to relay signals between said fixed station and said first mobile terminal and storing information relating to use of the second mobile as a relay.
- 20 15. A mobile terminal for communication with a fixed station included in a mobile communications network, said mobile terminal being configured to relay signals between said fixed station and another mobile terminal and to provide information to said network relating to its use as a relay.
- 25 16. A mobile terminal according to claim 15, wherein said terminal includes a first wireless interface for communicating with said fixed station.
17. A mobile terminal according to claim 16, wherein said terminal includes a
30 second, different wireless interface for communicating with said other mobile terminal.

18. A server associated with a mobile communications network for storing information relating to mobile terminals, said server configured to store relay information in response to a first mobile terminal exchanging signals with a fixed station included in said network via a second mobile terminal.

5

19. A method, in a mobile communications network, of rewarding a first mobile terminal for relaying signals between a second mobile terminal and either a third mobile terminal or a fixed station, the method comprising awarding credit to said first mobile terminal, wherein said credit is exchangeable for money or money's
10 worth.

20. A method according to claim 19, wherein said money's worth includes provision of communication service.

15 21. A mobile communications network for mobile terminals including a first mobile terminal for relaying signals between a second mobile terminal and either a third mobile terminal or a fixed station, the network being configured to award credit to said first mobile terminal, wherein said credit is exchangeable for money or money's worth, so as to reward said first mobile terminal for relaying said signals.

20

22. A network according to claim 21, wherein the network is configured to store information relating to said credit awarded.

23. A server associated with a mobile communications network which includes a
25 first mobile terminal for relaying signals between a second mobile terminal and either a third mobile terminal or a fixed station, the server being configured to award credit to said first mobile terminal, wherein said credit is exchangeable for money or money's worth, so as to reward said first mobile terminal for relaying said signals.

30

24. A mobile terminal for use in mobile communications network and for relaying signals between another mobile terminal and either yet another mobile terminal or a fixed station, said terminal being configured to award itself or be

awarded credit for relaying said signals, wherein said credit is exchangeable for money or money's worth.

25. A method, in a mobile communications network, of rewarding a first mobile
5 terminal for relaying signals between a second mobile terminal and either a third
mobile terminal or a fixed station, the method comprising extending call-time of
said first mobile terminal.

26. A method of operating a mobile communications network including a first
10 mobile terminal for relaying signals between a second mobile terminal and either a
third mobile terminal or a fixed station, the method comprising rewarding the first
mobile terminal for relaying said signals with increased network access.

27. A method according to claim 26, wherein said rewarding of the first mobile
15 terminal with increased network access comprises increasing call-time available to
the first mobile terminal.

28. A method according to claim 26, wherein said rewarding of the first mobile
terminal with increased network access comprises increasing data volume available
20 to the first mobile terminal.

1/8




FIG. 1




FIG. 12

2/8





FIG. 2

3/8



	User ID 1	User ID 2	...
Communication Charges	10	6	...
Relay Points	5	0	...

FIG. 4

	Relay 1	Relay 2	...
ID of Source Terminal	+44 7777 111 000	100.256.256.0	...
ID of Destination Terminal	+44 7777 333 000	101.256.256.0	...
Start Time	15:57:43	07:12:52	...
EndTime	16:02:38	07:13:11	...
ID of Relay Terminal 1	+44 7777 222 000	101.256.256.0	...
ID of Relay Terminal 2	<Empty>	101.256.256.0	...
...

FIG. 5

4/8




FIG. 6

5/8




FIG. 7

6/8




FIG. 8




FIG. 9

7/8




FIG. 10




FIG. 11

8/8




FIG. 13

INTERNATIONAL SEARCH REPORT

International Application No.

PCT/EP 01/15395

A. CLASSIFICATION OF SUBJECT MATTER
IPC 7 H04Q7/32 H04B7/26

According to International Patent Classification (IPC) or to both national classification and IPC

B. FIELDS SEARCHED

Minimum documentation searched (classification system followed by classification symbols)

IPC 7 H04Q H04B H04M

Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched

Electronic data base consulted during the international search (name of data base and, where practical, search terms used)

EPO-Internal, INSPEC, PAJ, IBM-TDB, WPI Data

C. DOCUMENTS CONSIDERED TO BE RELEVANT

Category *	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
A	DE 199 61 595 A (BOSCH GMBH ROBERT) 28 June 2001 (2001-06-28) column 3, line 2 - line 27; figure 1 ---	1,14,15, 19,21, 24-26
A	US 5 850 593 A (URATANI CHIKARA) 15 December 1998 (1998-12-15) column 1, line 48 -column 2, line 41 column 2, line 60 -column 3, line 23 column 4, line 64 -column 5, line 22; figures 1,3 ---	1,14,15, 19,21, 24-26
A	WO 01 22757 A (LEHTINEN OTTO ALEKSANTERI ;NOKIA NETWORKS OY (FI); JOKINEN HARRI ()) 29 March 2001 (2001-03-29) page 1, line 6 -page 4, line 8; figures 1,2 ---	1,14,15, 18,19, 21,23-26
	-/-	

☒ Further documents are listed in the continuation of box C.☒ Patent family members are listed in annex.

* Special categories of cited documents:

A document defining the general state of the art which is not considered to be of particular relevance

E earlier document but published on or after the international filing date

L document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)

O document referring to an oral disclosure, use, exhibition or other means

P document published prior to the international filing date but later than the priority date claimed

T later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention

X document of particular relevance; the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone

Y document of particular relevance; the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art.

& document member of the same patent family

Date of the actual completion of the international search

6 September 2002

Date of mailing of the international search report

13/09/2002

Name and mailing address of the ISA

European Patent Office, P.B. 5818 Patentlaan 2
NL - 2280 HV Rijswijk
Tel. (+31-70) 340-2040, Tx 31 651 epo nl,
Fax (+31-70) 340-3016

Authorized officer

Reeck, G

INTERNATIONAL SEARCH REPORT

International Application No

PCT/EP 01/15395

C.(Continuation) DOCUMENTS CONSIDERED TO BE RELEVANT

Category *	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
A	WO 01 62026 A (NOKIA MOBILE PHONES LTD ;JOKINEN HARRI (FI); LEHTINEN OTTO (FI); R) 23 August 2001 (2001-08-23) claims 8,9,18; figure 3B -----	1,14,15, 18,19, 21,23-26
A	WO 00 38443 A (KOPONEN PETTERI ;RAESAENEN JUHANNA (FI); ERICSSON TELEFON AB L M (S) 29 June 2000 (2000-06-29) abstract -----	1,14,15, 18,19, 21,23-26

INTERNATIONAL SEARCH REPORT

 International Application No
 PCT/EP 01/15395

Patent document cited in search report		Publication date		Patent family member(s)	Publication date
DE 19961595	A	28-06-2001	DE	19961595 A1	28-06-2001
			SE	0004678 A	22-06-2001
US 5850593	A	15-12-1998	CN	1126415 A ,B	10-07-1996
			GB	2291564 A ,B	24-01-1996
			JP	8084373 A	26-03-1996
			SG	32405 A1	13-08-1996
WO 0122757	A	29-03-2001	FI	992018 A	22-03-2001
			AU	7292800 A	24-04-2001
			WO	0122757 A1	29-03-2001
WO 0162026	A	23-08-2001	FI	20000355 A	17-08-2001
			AU	3746401 A	27-08-2001
			WO	0162026 A1	23-08-2001
WO 0038443	A	29-06-2000	AU	3047300 A	12-07-2000
			EP	1145576 A2	17-10-2001
			WO	0038443 A2	29-06-2000
			TR	200101836 T2	21-05-2002